Cisco Desk Phone 9800 Series






2

Contents

03	Product overview
04	Features and benefits
06	Platform support
06	Product specifications
19	Ordering information
21	Licensing
22	Warranty information
22	Product sustainability
23	Cisco Capital
23	For more information



Product overview

Product description

Cisco is bringing a new standard to desk phones with a portfolio built for working in modern office environments. The Desk Phone 9800 Series was designed with IT and facilities in mind to deliver four new phone models and one Key Expansion Module (KEM). Included on each phone is the newly released PhoneOS software that simplifies the user experience and compliments our video portfolios RoomOS devices to give a seamless experience from desk spaces to meeting rooms. With expanded functionality – the 9800 Series combines secure enterprise calling, meetings, desk reservations, sustainability, and emergency notifications all in one device. You don't need to buy a

dedicated device for each feature – all the features are built into each phone.

The Desk Phone 9800 Series reduces the complexity of purchasing, deploying, managing, and training. To further simplify, you can use one device for Cisco Unified Communications Manager (CUCM), Webex Calling, Broadworks, or other 3rd party cloud calling platforms. Alongside our extensive portfolio of desk devices, the 9800 series is uniquely positioned in the market to help transform the workplace by bridging the gap between hybrid work, calling, and meetings – and is the most cost-effective solution for workstations at scale.











Features and benefits

Table 1. Features and benefits

FEATURE	BENEFIT
One platform with PhoneOS	 One device and one software configured for all platforms - such as Cisco Unified Communications Manager (CUCM), Webex Calling, Broadworks, or other 3rd party cloud calling platforms. Deployments and setup easier for IT teams with the flexibility they require, providing a low-touch seamless experience to replace an existing phone with the 9800 series.
Desk reservation and hot desking	 Desk reservation and hot desking allow your organization to make the most of office real estate. People using shared workspaces can reserve, book, and sign into a desk for the day via their phone. Native sign-in/authentication to enable users to personalize their space by accessing their contacts, calendar, meetings, and personalized settings.
Action button	 Each phone includes a customizable action button designed for a variety of use cases: Instantly access essential scenarios such as emergency alerts, security, broadcast/paging and more. Configure up to three scenarios on a single action button for greater flexibility. Execute multiple actions with a single action button trigger. For example, initiate a phone call while launching a remote web application to send text messages to a group of contacts. Enable advanced interoperability with web applications through adaptable configuration fields.
Enhanced audio features including noise removal	 Al noise removal for all 9800 models. The 9861 and 9871 also supports Al noise removal for incoming audio. Enhances audio quality with Al by converting narrowband audio to wideband audio on the 9861 and 9871. Built-in speaker is enhanced by a larger speaker driver and new bassenhancing acoustic enclosure for more real, natural-sounding voices.
One button to join a meeting	Experience One Button to Push (OBTP) to quickly join meetings from the device's screen (applicable when registered to Webex Calling and CUCM).

 Table 1.
 Features and benefits

FEATURE	BENEFIT
Webex Companion	With the Webex desktop app and Cisco Desk Phone 9800 Series Companion, the end users can:
	 Enable video and view or share content via the Webex desktop app while keeping audio on the desk phone during a Webex meeting. Better control of the desk phone via the Webex desktop app: mute/unmute and adjust the phone volume.
Security	 Security is at the core of design with hardware-enabled security, runtime protection, application security, and industry compliance. Featuring Trusted Platform Module (TPM) 2.0 hardware, plus top-of-the-line security features such as TLS 1.3, Secure Boot, Image Authentication, and more.
Serviceability	 View detailed issues and diagnostics information on the phone UI. Built-in ThousandEyes Endpoint Agent on the 9861 and 9871 enabling network path monitoring.
Sustainability	 Leader for sustainable phones in the industry. Over 74% PCR, reduced and recyclable packaging, energy saving, and deep sleep features. Cisco takeback program which reduces e-waste and ensure that plastics can go back into recycled supply chain practices.
Language Al	 Enhance user experience with a Large Language Model: Enable live captions that allow users to view real-time transcriptions of dialogue during a Webex meeting. Display in-meeting summary and highlight action items during a Webex meeting. This feature is especially beneficial for participants joining midway, helping them stay informed and focused.
Accessibility	 Voice Feedback, which is supported in English, French, Italian, German and Spanish, assists people with vision impairments by providing voice prompts for phone navigation, caller ID, button functions, and more. Adjustable font size makes text easier to read and navigate.

Platform support

Table 2. Cisco Desk Phone 9800 series backend calling server support

PLATFORMS SUPPORTED	CERTIFICATIONS
Cisco Webex Calling	Interoperability Tested and Certified
Cisco Unified Communication Manager (CUCM) 12.5 or above*	Interoperability Tested and Certified
Webex Dedicate Instance (DI)	Interoperability Tested and Certified
Cisco BroadWorks	Interoperability Tested and Certified
Microsoft SIP Gateway	Microsoft SIP Gateway Compatible
Asterisk	Interoperability Tested and Certified

^{*}Not all CUCM versions support Cisco Desk Phone 9800 Series natively, dev pack and device enabler file (QED) might be required.

Product specifications

Table 3. Product specifications

FEATURES	SPECIFICATIONS
Display	 9841: 3.5-inch Grayscale LCD, 384 x160 resolution, backlit 9851: 3.7-inch Color LCD, 480 x 240 resolution, backlit 9861: 5-inch Color LCD, 800 x 480 resolution, backlit 9871: 5-inch Color Touch LCD, 1280 x 720 resolution, backlit 9800 KEM: 5-inch Color LCD, 480 x 800 resolution, backlit
Audio (*may vary depending on the codec)	 Frequency response: 100 Hz - 20 kHz for handsfree speaker FEC (Forward Error Correction) AEC (Acoustic Echo Cancellation) AGC (Automatic Gain Control) CNG (Comfort Noise Generation) VAD (Voice Activity Detection) PLC (Packet Loss Concealment) Silence Suppression* Acoustic Shock Protection (Handset/headset) Adaptive Jitter Buffer Dual Tone Multi-Frequency (DTMF) tone generation (RFC 2833 and in-band) Cisco HD audio, TIA-810/920 and ETSI ES 202 737/738/739/740 compliant

Table 3. Product specifications

FEATURES	SPECIFICATIONS
	 Cisco smart audio Conventional and Al based background noise and voice removal for sending side Conventional and Al based background noise removal for receiving side (9861 and 9871) Enhances the in-call experience for PSTN calls by extending low-fidelity (narrowband) audio to high-definition (wideband) (9861 and 9871) Ultrasonic support HAC (Hearing Aid Compatible) handset
Audio codec support	· OPUS, G.722, G.722.2, iSAC, G.711(a-law/μ-law), G.729a/b, and iLBC
Physical Line Keys	 9841: 4 9851: 6 9861: 10 9871: N/A 9800 KEM: 20 (2 pages)
Maximum of supported line and programmable line keys	 9841: 4 9851: 46 9861: 130 9871: 128
Maximum of supported SIP lines	130 for CUCM and Webex DI16 for Webex Calling and Open SIP platforms
Hard keys	 Action button Calendar button (9851 and 9861) Favorite button Hold/Resume, Transfer, and Conference keys Application key Directory key Standard keypad Volume-control toggle key Speakerphone, Headset, and Mute keys Navigation and Select key (9841, 9851 and 9861) Home button (9871 only) Page keys (9800 KEM only)

FEATURES	SPECIFICATIONS
Backlit indicator	 The phones support backlit indicator for the physical buttons of Speakerphone, Headset and Mute, Calendar (9851 and 9861), Select (9841, 9851 and 9861) and Home (9871 only) as well as the line keys. The phones also support two specific LEDs, Front arc LED and Top LED, to indicate the device status, including message waiting, missed call, hot desk availability, etc.
Handset	 Wideband-capable audio handset (connects through the phone's dedicated handset RJ-9 port). The handset coiled cord has a custom end for concealed cable routing beneath the phone (cord length is approximately 21 in. [55 cm (about 1.8 ft)] coiled and up to 72 in. (183 cm (about 6 ft)) extended). The handset is Hearing Aid-Compatible (HAC) and meets Federal Communications Commission (FCC Part 68) requirements for the Americans with Disabilities Act (ADA). You can achieve Section 508 loudness requirements by using industry-standard inline handset amplifiers such as Walker Equipment W-10 or CE-100 amplifiers.
Dial pad	The dial pad is ADA-compliant.
Speakerphone	 The full-duplex speakerphone provides flexibility in placing and receiving calls handsfree. For added security, the audible Dual Tone Multifrequency (DTMF) tones are masked when the speakerphone mode is used.
USB and Aux port	 9841: One USB-A port: The USB-A port provides 0.25A power output at 5V or 1.25W under PoE, and 0.5A power output at 5V or 2.5W when using the Cisco Power Adapter 3 (local power supply). One Auxiliary port (console log collection only). 9851: One USB-A port: The USB-A port provides 0.5A power output at 5V or 2.5W under PoE, and 1A power output at 5V or 5W when using the Cisco Power Adapter 3 (local power supply). One USB-C port: The USB-C port provides 0.5A power output at 5V or 2.5W under PoE or when using the Cisco Power Adapter 3 (local power supply). 9861 and 9871: One USB-A port: The USB-A port provides 0.5A power output at 5V or 2.5W under PoE, and 1.3A power output at 5V or 6.5W when using the Cisco Power Adapter 3 (local power supply). One USB-C port: The USB-C port provides 0.5A power output at 5V or 2.5W under PoE or when using the Cisco Power Adapter 3 (local power supply).

FEATURES	SPECIFICATIONS
	 9800 KEM: One USB-A female port: When one 9800 KEM connected with the 9851, the USB-A port provides 0.15A power output at 5V or 0.75W under PoE, and 0.5A power output at 5V or 2.5W when using the Cisco Power Adapter 3 (local power supply). When one 9800 KEM is connected with the 9861 or 9871, the USB-A port provides 0.15A power output at 5V or 0.75W under PoE, and 1A power output at 5V or 5W when using the Cisco Power Adapter 3 (local power supply). When two 9800 KEMs are connected with the 9861 or 9871, the USB-A port provides 0.5A power output at 5V or 2.5W when using the Cisco Power Adapter 3 (local power supply). When three 9800 KEMs are connected with the 9861 or 9871, the USB-A port provides 0.15A power output at 5V or 0.75W when using the Cisco Power Adapter 3 (local power supply). One USB-A male port: The USB-A port on 9800 KEM draws power from the phone's USB-A port under PoE or when using the Cisco Power Adapter 3 (local power supply). The charging capability depends on the maximum output power of the USB port on the phone in various deployment modes. If a connected device attempts to draw more power than the USB port's maximum output, a warning message will pop up, prompting you to unplug the device.
Ethernet switch	 An internal 2-port Cisco Ethernet switch allows for a direct connection to a 10/100/1000BASE- T Ethernet network (IEEE 802.3i/802.3u/802.3ab) through an RJ-45 interface with single LAN connectivity for both the phone and a colocated PC. The system administrator can designate separate VLANs (IEEE 802.1Q) for the PC and phone, providing improved security and reliability of voice and data traffic.

FFATUREO	
Bluetooth® wireless Technology*	 The 9861 and 9871 (excluding no-radio variants) feature Bluetooth wireless technology Bluetooth version: 5.2 (Bluetooth® Low Energy) Bluetooth Enhanced Data Rate (EDR) Bluetooth Class 1 Support for Wideband and Narrowband codecs Bluetooth Profiles: Hands-Free Profile (HFP) Advanced Audio Distribution Profile (A2DP) Human Interface Device Profile (HID) Phone Book Access Profile (PBAP)
Wi-Fi®	 The 9861 and 9871 (excluding no-radio variants) are Wi-Fi CERTIFIED™ supporting 802.11a/b/g/n/ac, 2.4 GHz / 5 GHz dual bands. Authentication: WPA (Wi-Fi Protected Access), WPA2 (Wi-Fi Protected Access II), and WPA3 (Wi-Fi Protected Access III) in both Personal and Enterprise modes Extensible Authentication Protocol - Flexible Authentication via Secure Tunneling (EAP-FAST) Protected Extensible Authentication Protocol - Generic Token Card (PEAP-GTC) Protected Extensible Authentication Protocol - Microsoft Challenge Handshake Authentication Protocol Version 2 (PEAP-MSCHAPv2) Extensible Authentication Protocol - Transport Layer Security (EAP-TLS) Encryption: Temporal Key Integrity Protocol (TKIP) and Message Integrity Check (MIC) Advanced Encryption Standard (AES) Robust management frame protection: BIP-CMAC-128 Wi-Fi standards: IEEE 802.11 a,b,d,e,g,h,i,n,r,ac Wi-Fi MultiMedia (WMM) Unscheduled Automatic Power Save Delivery (UAPSD) Antenna Type: Dipole (On-Board) Antenna Gain (dBi): 9861: 2.4G: 3:06 5G: 4.11 9871: 2.4G: 3.22 5G: 4.23

FEATURES	SPECIFICATIONS
	 Frequency Band (MHz) 9861: - 2.4G: 2412.0 - 2472.0 5G: 5150.0 - 5250.0, 5250.0 - 5350.0, 5470.0 - 5725.0, 5745.0 - 5825.0 9871: - 2.4G: 2412.0 - 2472.0 5G: 5150.0 - 5250.0, 5250.0 - 5350.0, 5470.0 - 5725.0, 5745.0 - 5825.0 Maximum EIRP for Mexico (dBm) 9861: - 2.4G: 20.05 - 5G: 17.03 9871: - 2.4G: 20.19 - 5G: 17.21
Power	 IEEE Power over Ethernet class 2 (9841) IEEE Power over Ethernet class 3 (9851, 9861 and 9871) Input rating: 0.42A, 48V DC The phones are compliant with EU lot-6 and lot-26
Key Expansion Module (KEM) compatibility and power	 The 9800 KEM doesn't have its own local power; the KEM power is provided from the host phone. 9851: IEEE Power over Ethernet class 3 or Cisco Power Adapter 3, enables one KEM via the USB-A port. 9861 and 9871: IEEE Power over Ethernet class 3, enables one KEM via the USB-A port. Cisco Power Adapter 3, enables up to three KEMs via the USB-A ports.

FEATURES	SPECIFICATIONS
Key features	· Caller ID
_	Call waiting
(*may vary	Call hold/resume
depending on	Music on Hold (MoH)
registered calling	Mute/unmute
platform)	• E.164/Plus Dialing
	Call forward
	Do not disturb
	Call back
	Call park
	Hold/Park Reversion
	Call pickup
	Transfer
	· Conference
	· Meet me
	Call preservation mode
	Speed dial
	Busy Lamp Field (BLF)
	· Redial
	Recording
	Barge and cBarge (conference barge)
	• Paging*
	Extension Mobility and EMCC* It was a reason.
	Hunt group Hunifarra Danas and artifact (LIDI) attaliant
	Uniform Resource Identifier (URI) dialing CMS mute support
	CMS mute sync*Voicemail
	Shared line
	• Privacy*
	Local call history
	Remote call history*
	Directory search
	Favorite contacts*
	Adjustable ring tones and volume levels
	Adjustable display brightness
	Time and date display
	Time zone settings*
	• E.911
	• Intercom*

FEATURES	SPECIFICATIONS
	Confidential Access Level (CAL)*
	Help desk on favorite button
	· Anti-spam*
	Hoteling*
	Flexible seating*
	 Voice feedback (multi-language support)
	 Webex features: unified call history, unified directory, hybrid calendar, meetings
	OBTP (One Button To Push) meetings
	In-meeting transcription (9861 and 9871)
	Webex In-Meeting Summary (9861 and 9871)
	Hot desking
	Cisco Spaces Hot Desking pre-booking*
	Remote Reboot
	Remote Factory Reset
	 Metrics for analytics and debugging*
	 Hotline*
	XSI/XML Application
	• FAC/CMC*
	Multicast Paging*
	 Support for Call center agent's phone*
	Adjustable font size
	Cisco IP Manager Assistant*
	• Switch the operating mode*
	Custom wallpaper and logo (9851, 9861 and 9871) Custom wallpaper and logo (9851, 9861 and 9871)
	• Pagination* (9851 and 9861)
	User Preference Attribute* Ois as I Lead at Count Deliving (0001 and 0071)
	Cisco Headset Smart Pairing (9861 and 9871) Makility *
	• Mobility*
	· XAPI
	Cisco Smart Power Framework Always use multi-line mode (9851, 9861 and 9871)
	 Always use multi-line mode (9851, 9861 and 9871) Customizable New call softkey for connected call state*
	 Customizable New call softkey for connected call state* Shared Call Appearance label config*
	 Shared Call Appearance label config* Dialog-based shared line appearance*
	Enhanced menu customization*
	 Call Queues and Customer Assist support*
	San quouso and odotomor resist support

FEATURES	SPECIFICATIONS
Network features	 Session Initiation Protocol (SIP) for signaling Session Description Protocol (SDP) IPv4 and IPv6 IPv6 Ready logo and USGv6 R1 compliant* Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Secure Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS) Dynamic Host Configuration Protocol (DHCP) client or static configuration Gratuitous Address Resolution Protocol (GARP) Domain Name System (DNS) Trivial File Transfer Protocol (TFTP) Secure HTTP (HTTPS) VLAN Real-Time Transport Protocol (RTCP) Cisco Discovery Protocol LLDP (including LLDP Media Endpoint Discovery [LLDP-MED]) Switch speed auto-negotiation Span to PC Network traverse (ICE, NAT and STUN)*
Deployment and serviceability features	 Native phone migration* Peer firmware sharing upgrade Problem report tool ThousandEyes integration (9861 and 9871) SRST support* MRA support* User credentials persistent for Expressway sign-in* Activation code onboarding WxC outbound proxy survivability support* NFC onboarding Cisco headset upgrade Enhanced Control Hub Status and Desk Phone Diagnostics*

FEATURES	SPECIFICATIONS
Security	 Secure boot 802.1x with Custom Device Certificate SIP OAuth Secure credential storage Device authentication Configuration file authentication and encryption Image authentication Random bit generation Secure Unique Device Identifier (SUDI) Signaling authentication and encryption using TLS Media authentication and encryption using SRTP HTTPS for client and server Configurable minimum TLS version Local Phone Unlock Password* Trusted Platform Module 2.0 Security-Enhanced Linux FIPS 140-2, 140-3 and UCR 2013 compliant TLS 1.3 and TLS client/server min version Secure erase On device Firewall* Assured Services SIP (AS-SIP)* Multilevel Precedence and Preemption (MLPP)* ECC* Disabling speakerphone, headset, and handset* Multi-server (SAN) Tomcat Certificate* No password warning* Device security insights*
	 HTTP proxy* VPN* Device Security Insights* LLDP MED Location Information Service for E911*
Physical dimensions (H × W × D)	 9841: 8.4 x 8.4 x 1.9 in. (214.0 x 214.0 x 49.4 mm) 9851: 8.9 x 8.4 x 1.9 in. (226.0 x 214.0 x 49.4 mm) 9861: 8.9 x 9.0 x 1.9 in. (226.0 x 230.0 x 49.4 mm) 9871: 8.9 x 8.4 x 1.9 in. (226.0 x 214.0 x 49.4 mm) 9800 KEM: 8.9 x 5.0 x 1.9 in. (226.0 x 126.0 x 48.5 mm)

FEATURES	SPECIFICATIONS
Weight	 9841: 954g 9851: 968g 9861: 1095g 9871: 1055g 9800 KEM: 483g
Phone-casing composition	 Polycarbonate Acrylonitrile Butadiene Styrene (ABS) textured plastic; Cosmetic class A
Operating temperature	- 32 to 104°F (0 to 40°C)
Nonoperating temperature shock	• 14 to 140°F (-10 to 60°C)
Humidity	Operating 10 to 90%, noncondensingNonoperating 10 to 95%, noncondensing
Language Support	 Arabic (Saudi Arabia) Bulgarian (Bulgaria) Catalan (Spain) Croatian (Croatia) Czech (Czech Republic) Danish (Denmark) Dutch (Netherlands) English (United Kingdom) English (United States) Estonian (Estonia) Finnish (Finland) French (France) French (Canada) German (Germany) Greek (Greece) Hebrew (Israel) Hungarian (Hungary) Italian (Italy) Japanese (Japan) Korean (Korea Republic) Latvian (Latvia) Lithuanian (Lithuania)

FEATURES	SPECIFICATIONS
	 Norwegian (Norway) Polish (Poland) Portuguese (Brazil) Portuguese (Portugal) Romanian (Romania) Russian (Russian Federation) Serbian (Republic of Serbia) Simplified Chinese (China) Slovak (Slovakia) Slovenian (Slovenia) Spanish (Colombia) Spanish (Spain) Swedish (Sweden) Thai (Thailand) Traditional Chinese (Hong Kong) Traditional Chinese (Taiwan) Turkish (Türkiye) Ukrainian (Ukraine) Welsh (United Kingdom)
Certification and compliance	 CE Markings per directives 2014/53/EU, 2014/35/EU and 2014/30/EU Safety UL60950, UL62368-1 CAN/CSA-C22.2 No. 60950 CAN/CSA 62368-1 EN/IEC 62368 AS/NZS 62368 EMC - Emissions 47CFR Part 15 (CFR 47) Class B AS/NZS CISPR32 Class B CISPR32: 2015 Class B EN 55032:2015+A11:2020 Class B ICES003 Class B VCCI Class B EN61000-3-2 EN61000-3-3 KS C 9832 VCCI-CISPR 32

FEATURES SPECIFICATIONS • EMC - Immunity - EN 55035:2017+A11:2020 Class B - KS C 9835 - Armadillo Light · FIPS compliant Telecom - FCC Part 68 HAC - CS-03-HAC - AS/ACIF S004 - AS/ACIF S040 - NZ PTC 220 - Industry Standards: TIA-810 and TIA-920 - Industry Standards: IEEE 802.3 Ethernet, IEEE 802.3af and 802.3at - Korea (RRA Public Notification 2020-6, Sep. 25th, 2020) - Korea (RRA Announce 2022-1, Jan. 3, 2022) Radio - FCC Part 15.247 - FCC Part 15.407 - FCC Part 2.1091 (BT RF Exposure TR) - RSS-102 (BT RF Exposure TR) - RSS-247 - EN 300 328 - EN 301893 - EN 300 330 - EN 62311 - EN 50665 - EN 301 489-1 - EN 301 489-3 - EN 301 489-17 - Korea (KS X 3123:2022, KS X 3124:2020, KS X 3126:2020) - STD-T66 - STD-T71

Ordering information

Table 4. Ordering information

PART NUMBER	PRODUCT DESCRIPTION
Desk Phone 9800 Series Main O	ffer Summary
DP-9841-K9=	Cisco Desk Phone 9841, Carbon Black
DP-9841-L-K9=	Cisco Desk Phone 9841, First Light
DP-9851-K9=	Cisco Desk Phone 9851, Carbon Black
DP-9851-L-K9=	Cisco Desk Phone 9851, First Light
DP-9861-K9=	Cisco Desk Phone 9861, Carbon Black
DP-9861-L-K9=	Cisco Desk Phone 9861, First Light
DP-9861NR-K9=	Cisco Desk Phone 9861, No Radio, Carbon Black
DP-9871-K9=	Cisco Desk Phone 9871, Carbon Black
DP-9871-L-K9=	Cisco Desk Phone 9871, First Light
DP-9871NR-K9=	Cisco Desk Phone 9871, No Radio, Carbon Black
Desk Phone 9800 Series TAA Mo	odel Offer Summary
DP-9841-K9++=	Cisco Desk Phone 9841, with NFC, TAA, Carbon Black
DP-9841NR-K9++=	Cisco Desk Phone 9841, No NFC, TAA, Carbon Black
DP-9851-K9++=	Cisco Desk Phone 9851, with NFC, TAA, Carbon Black
DP-9851NR-K9++=	Cisco Desk Phone 9851, No NFC, TAA, Carbon Black
DP-9861-K9++=	Cisco Desk Phone 9861, TAA, Carbon Black
DP-9861NR-K9++=	Cisco Desk Phone 9861, No Radio, TAA, Carbon Black
DP-9871-K9++=	Cisco Desk Phone 9871, TAA, Carbon Black
DP-9871NR-K9++=	Cisco Desk Phone 9871, No Radio, TAA, Carbon Black

Table 4. Ordering information

PART NUMBER	PRODUCT DESCRIPTION			
Desk Phone 9800 Series Custom	nized Model Offer Summary			
DP-9841-K9=	Cisco Desk Phone 9841, Customized Model, Carbon Black			
DP-9841NR-K9=	Cisco Desk Phone 9841, NoNFC, Customized Model, Carbon Black			
DP-9851-K9=	Cisco Desk Phone 9851, Customized Model, Carbon Black			
DP-9851NR-K9=	Cisco Desk Phone 9851, NoNFC, Customized Model, Carbon Black			
DP-9861-K9=	Cisco Desk Phone 9861, Customized Model, Carbon Black			
DP-9861NR-K9=	Cisco Desk Phone 9861, NoRadio, CustomizedModel, CarbonBlack			
DP-9871-K9=	Cisco Desk Phone 9871, Customized Model, Carbon Black			
DP-9871NR-K9=	Cisco Desk Phone 9871, NoRadio, CustomizedModel, CarbonBlack			
Desk Phone 9800 Series Arabic	Model Offer Summary			
DP-9861-A-K9=	Cisco Desk Phone 9861, Arabic Layout, Carbon Black			
DP-9871-A-K9=	Cisco Desk Phone 9871, Arabic Layout, Carbon Black			
Desk Phone 9800 Series Access	ories (Optional - Ordered Separately)			
DP-9800-KEM=	Cisco Desk Phone 9800 Key Expansion Module, Carbon Black			
DP-9800-WMK=	Cisco Desk Phone 9800 Wall Mount Kit			
DP-9800-KEM-WMK=	Cisco Desk Phone 9800 Wall Mount Kit for Key Expansion Module			
DP-9800-WMK-88ADP=	Cisco Desk Phone 9800 Wall Mount Kit Adapter for 8800 Phones			
Desk Phone 9800 Series Local P	ower SPAREs (Optional - Ordered Separately)			
CP-PWR-ADPT-3-AR=	Cisco Power Adapter 3 with Argentina Clip			
CP-PWR-ADPT-3-AU=	Cisco Power Adapter 3 with Australia Clip			
CP-PWR-ADPT-3-BZ=	Cisco Power Adapter 3 with Brazil Clip			
CP-PWR-ADPT-3-CN=	Cisco Power Adapter 3 with China Clip			

Table 4. Ordering information

PART NUMBER	PRODUCT DESCRIPTION
CP-PWR-ADPT-3-EU=	Cisco Power Adapter 3 with European Clip
CP-PWR-ADPT-3-IN=	Cisco Power Adapter 3 with India Clip
CP-PWR-ADPT-3-KR=	Cisco Power Adapter 3 with Korea Clip
CP-PWR-ADPT-3-NA=	Cisco Power Adapter 3 with North America Clip
CP-PWR-ADPT-3-UK=	Cisco Power Adapter 3 with United Kingdom Clip
Desk Phone 9800 Series Replac	ement SPAREs
DP-9800-HS=	Desk Phone 9800 Replacement Handset, Carbon Black-SPARE
DP-9800-HS-L=	Desk Phone 9800 Replacement Handset, First Light -SPARE
DP-9800-CORD=	Desk Phone 9800 Replacement Handset Cord, Carbon Black-SPARE
DP-9800-CORD-L=	Desk Phone 9800 Replacement Handset Cord, First Light -SPARE
DP-9800-FS=	Desk Phone 9841 & 9851 Replacement Footstand, Carbon Black-SPARE
DP-9861-FS=	Desk Phone 9861 Replacement Footstand, Carbon Black - SPARE
DP-9871-FS=	Desk Phone 9871 Replacement Footstand, Carbon Black - SPARE

Table 5. Package Dimensions, Weights and Piece Counts

	GIFTBOX			OVERPACK				PALLET							
PRODUCT	Length (cm)	Width (cm)	Height (cm)	Weight (kg)	Box pcs per overpack	Length (cm)	Width (cm)	Height (cm)	Weight (kg)	Over pack pcs per pallet	Length (cm)	Width (cm)	Height (cm)	Weight (kg)	Phones per Pallet
9841	31.5	24	7.8	1.3	10	50	40	34	14.3	18	120	100	114	275	180
9851	31.5	24	7.8	1.4	10	50	40	34	14.4	18	120	100	114	276.2	180
9861	31	24.5	7.2	1.5	8	60.1	32.1	26.4	12.9	24	121.9	101.6	1175	332.6	192
9871	29.1	24.5	7.2	1.5	8	60.1	30.4	26.4	12.7	24	121.9	101.6	1175	327.8	192
9800 KEM	25.4	17.3	8.13	0.71	18	54	50.42	28.45	13.3	12	121.9	101.6	997	182.6	216

Licensing

All Cisco Desk Phone 9800 Series are covered by the Cisco End User License Agreement at www.cisco.com/c/en/user_license_agreement.html.

Or use the shortcut: www.cisco.com/go/eula.

Warranty information

The Desk Phone 9800 Series are covered by a Cisco 1-Year Limited Hardware Warranty (details at: www.cisco.com/go/warranty).

Product sustainability

Information about Cisco's Environmental, Social and Governance (ESG) initiatives and performance is provided in Cisco's CSR and sustainability reporting.

 Table 6.
 Cisco Environmental Sustainability Information

SUSTAINABILITY TOPIC	REFERENCE
Information on product-material-content laws and regulations	<u>Materials</u>
Information on electronic waste laws and regulations, including our products, batteries, and packaging	WFFF Compliance

Table 7. Product Sustainability Features and Certifications

FEATURES	SPECIFICATIONS
Energy Saving Solutions	 The phones support the display off and deep sleep modes. Display off mode power consumption: 9841: 2.35W when using the Cisco Power Adapter 3 (local power supply) and 1.95W under PoE 9851: 2.82W when using the Cisco Power Adapter 3 (local power supply) and 2.69W under PoE 9861: 3.48W when using the Cisco Power Adapter 3 (local power supply) and 3.26W under PoE 9871: 3.5W when using the Cisco Power Adapter 3 (local power supply)
	 and 3.16W under PoE Deep sleep mode power consumption: 9841: 0.26W when using the Cisco Power Adapter 3 (local power supply) and 0.61W under PoE 9851: 0.27W when using the Cisco Power Adapter 3 (local power supply) and 0.69W under POE 9861: 0.27W when using the Cisco Power Adapter 3 (local power supply) and 0.79W under PoE 9871: 0.27W when using the Cisco Power Adapter 3 (local power supply) and 0.8W under PoE

 Table 7.
 Product Sustainability Features and Certifications

FEATURES	SPECIFICATIONS			
Carbon Emission Insights	 The phones support to report the power consumption data and the organization's carbon footprint can be shown on the Cisco Webex Control Hub. 			
Certification and compliance	 ENERGY STAR® EU Lot-6 EU Lot-26 			

Cisco Capital

Flexible payment solutions to help you achieve your objectives.

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services, and complementary third-party equipment in easy, predictable payments. Learn more.



For more information

Please visit https://www.webex.com/cisco-phone-9800series.html.

Date: July 2025

C78-4253749-04